

# SunPumps HS Series Submersible Pump

## Model HS-22-308

Performance Data — U.S. Units (GPM / Feet / Watts)

| Input Power | TDH 131 ft | TDH 161 ft | TDH 197 ft | TDH 230 ft | TDH 262 ft | TDH 295 ft | TDH 328 ft | TDH 361 ft |
|-------------|------------|------------|------------|------------|------------|------------|------------|------------|
| P1 (Watts)  | GPM        | GPM        | GPM        | GPM        | GPM        | GPM *      | GPM *      | GPM *      |
| <b>300</b>  |            |            |            |            |            |            |            |            |
| <b>600</b>  | 12.4       | 9.4        | 2.2        |            |            |            |            |            |
| <b>900</b>  | 17.0       | 14.6       | 11.8       | 7.5        |            |            |            |            |
| <b>1200</b> | 20.5       | 18.2       | 15.8       | 12.8       | 10.1       |            |            |            |
| <b>1500</b> | 23.4       | 21.2       | 18.9       | 16.2       | 13.9       | 9.9        | 6.7        |            |
| <b>1800</b> | 26.0       | 23.7       | 21.5       | 18.9       | 16.7       | 13.6       | 11.3       | 8.8        |
| <b>2100</b> | 28.3       | 26.0       | 23.8       | 21.3       | 19.1       | 16.4       | 14.2       | 12.0       |
| <b>2400</b> | 30.4       | 28.1       | 25.8       | 23.3       | 21.2       | 18.7       | 16.6       | 14.4       |
| <b>2700</b> | 32.4       | 30.0       | 27.7       | 25.2       | 23.1       | 20.8       | 18.6       | 16.4       |
| <b>3000</b> |            |            |            |            |            |            |            |            |

\* Dashed curves (TDH 295/328/361 ft) denote reduced-flow / extended-head operating range. Values approximated from reference performance curve; verify against factory test data before publishing to customers.

# SunPumps HS Series Submersible Pump

Model HS-22-308 — Performance Curve (U.S. Units)

## HS-22-308 Performance Curve

